



FLEX HOSE *selector table*

FEATURES									
PRODUCT	Core (1)	reinforcement	PSI	diam	length	service	applications	options	additions
Super Mining Flex	1/2"@ ≤12" 1"@ ≥12"	steel ring	200 or 300	4" to 30"	40 ft	suction & discharge	Pit & field or line pump suction hose. Booster pump lines in place of pipe. Dredge suction.	500 PSI, 300# flanges or rotating, SBR tube	reducing sizes, outlets, pressure taps, drains
Mining Flex	1/2"@ ≤12" 1"@ ≥12"	steel spring	200 300 500	4" to 60"	40 ft	suction & discharge	Matrix & tailing pump Replace multiple fittings and rigid pipe	300# flanges or rotating / SBR, neoprene, nitrile, hypalon, chlorobutyl, E	reducing sizes, outlets, pressure taps, drains
Series 1000	optional	helical wire	150	4" to 24"	40 ft	suction & discharge	In-plant	300# flanges or rotating / SBR, neoprene, nitrile, hypalon, chlorobutyl, E	reducing sizes, outlets, pressure taps, drains
Corrugated hose	1/2 inch gum rubber	helical wire	150	4.5" to 24"	10ft 20ft 40ft	suction & discharge	Discharge to sumps and settling tanks	other flanges	Not rubber or neoprene wear tube
Series 8000	optional	spring steel	150	2" to 84"	24 inch	suction & discharge	Replace rigid pipe reduce pump vibration	300# flanges or rotating, lateral offsets / SBR, neoprene, nitrile, hypalon, chlorobutyl, E	reducing sizes, eccentric design
Town-i-flex reducing hose	optional	spring steel	150	6" to 48"	20'	suction & discharge	Replace rigid pipe reduce pump vibration	300# flanges or rotating	reducing sizes, eccentric design
Series 9000	Towniprene 1/2 inch tube	spring steel	150	2" to 84"	24 inch	suction & discharge	Replace rigid pipe reduce pump vibration	300# flanges or rotating, lateral offsets	reducing sizes, eccentric design
Flotation hose	std	Polyester cord fabric	150	4" to 30"	40'	discharge	self-floating hose	300# flanges or rotating	300PSI optional
Town-I flex laterals & Tees	optional	spring steel	200-600	Contact Townley	Contact Townley	suction & discharge	Replace rigid pipe	300# flanges or rotating	reducing sizes, outlets, pressure taps, drains

(1) Standard features: gum rubber wear tube, polyester reinforcing cord, SBR finish coating