

# TOWNLEY MANUFACTURING CO., INC. RUBBER HOSE & FITTINGS

### MINING/DREDGING FLEXIBLES



**FOR HEAVY-DUTY MINING & DREDGING APPLICATIONS**

- Suction & Discharge - 200 - 600 PSI
- VARIETY OF END OPTIONS
- 4" - 36" I.D. Lengths to 40 feet

### SUPER MINING FLEXIBLE



**TWICE AS FLEXIBLE AS STANDARD MINING FLEXIBLE**

- Mining & Dredging Applications
- Higher Pressure Rating On Request
- Suction & Discharge to 200PSI
- Lengths to 40 feet

### 6000XL125 SLURRY HOSE




**FOR IN-PLANT PIPELINE APPLICATIONS**

- Suction & Discharge Applications 125 - 150 PSI
- VARIETY OF END OPTIONS
- 4" - 30" I.D. Lengths to 40 feet

### TOWN-I-FLOAT BALLS

Foam-filled polyethylene Balls for hose & pipeline support in the water. Long lasting easy to install & maintain



### SELF-FLOATING DREDGE DISCHARGE HOSE



**BUILT-IN FLOTATION**

- 150 - 300 PSI
- 4" - 30" I.D.
- Lengths to 40 feet

### DREDGE DISCHARGE SLEEVES

**FOR DISCHARGE APPLICATIONS ONLY**  
Plain, Bell, or Soft Ends 150 PSI  
HOSE I.D. = PIPE O.D.  
4 1/2" - 24" I.D. Lengths to 40 feet



### RUBBER ELBOWS

11.5 to 180 degree 3" - 24" I.D. - 100 PSI  
For Cyclone Overflow  
3" - 20" I.D. - 100PSI

### 1000XL SUCTION FLEXIBLES



**FOR IN-PLANT PUMP APPLICATIONS**  
Suction & Discharge to 150 PSI  
4" - 24" I.D. - Lengths to 40 feet

### RUBBER EXPANSION JOINTS



1 1/2" - 60" I.D.  
Lengths 6" - 24" 150 PSI

### OPTIONS



**HOSE WITH CLEAN-OUT LATERAL**



**CORRUGATED STYLE FOR EXTRA FLEXIBILITY**



**REDUCING STYLE**



Plain Ends



Soft Ends



Enlarged Or Bell Ends



Built-In, Rubber-Lined Flanged Steel Nipple



Built-In Unlined Steel Nipple, Victaulic Ends



Built-In Rubber-Lined Steel Nipple With Rotating Flange

### TUBE OPTIONS

- Natural Gum Rubber
- SBR
- Neoprene
- Nitrile
- Chlorobutyl
- Hypalon
- Triflex Hi-Temp Rubber

### \*ALSO AVAILABLE \*

- Pinch Tubes
- Waterjack Hose
- LP 2000 Low-Pressure Hose